

Vamzdynai priešgaisrinėms sistemoms

Rifliuotas karšto cinkavimo vamzdis 6 m, SBSC / FG / FG



Kodas	DN	Dyxt	Svoris/m	Svoris/6m	Aprašymas	Kaina
NF-G-32	DN 32	42,4x2,0	2,1 kg	12,6 kg	Cinkuotas vamzdis, NF L=6000, 42,4 x 2,0	7,10
NF-G-40	DN 40	48,4x2,0	2,4 kg	14,5 kg	Cinkuotas vamzdis, NF L=6000, 48,3 x 2,0	8,09
NF-G-50	DN 50	60,3x2,0	3,0 kg	18,3 kg	Cinkuotas vamzdis, NF L=6000, 60,3 x 2,0	10,36
NF-G-65	DN 65	76,1x2,0	3,9 kg	23,3 kg	Cinkuotas vamzdis, NF L=6000, 76,1 x 2,0	13,24
NF-G-80	DN 80	88,9x2,0	4,5 kg	27,1 kg	Cinkuotas vamzdis, NF L=6000, 88,9 x 2,0	15,32
NF-G-100	DN 100	114,3x2,3	6,7 kg	40,2 kg	Cinkuotas vamzdis, NF L=6000, 114,3 x 2,3	22,69
NF-G-125	DN 125	139,7x2,9	10,3 kg	61,7 kg	Cinkuotas vamzdis, NF L=6000, 139,7 x 2,9	38,00
NF-G-150	DN 150	168,3x2,9	12,5 kg	75,0 kg	Cinkuotas vamzdis, NF L=6000, 168,3 x 2,9	42,60
NF-G-200	DN 200	219,1x3,6	20,1 kg	120,3 kg	Cinkuotas vamzdis, NF L=6000, 219,1 x 3,6	74,61

Rifliuotas, dažytas RAL7012, I vamzdis 6m, SBSC / FM / FG



Kodas	DN	Dyxt	Svoris/m	Svoris/6m	Aprašymas	Kaina
NF-EPOXY-32	DN 32	42,4x2,0	2 kg	12,00 kg	Dažytas vamzdis, NF L=6000, 42,4 x 2,0	6,20
NF-EPOXY-40	DN 40	48,4x2,0	2,3 kg	13,80 kg	Dažytas vamzdis, NF L=6000, 48,3 x 2,0	7,07
NF-EPOXY-50	DN 50	60,3x2,0	2,9 kg	17,40 kg	Dažytas vamzdis, NF L=6000, 60,3 x 2,0	8,90
NF-EPOXY-65	DN 65	76,1x2,0	3,7 kg	22,22 kg	Dažytas vamzdis, NF L=6000, 76,1 x 2,0	11,31
NF-EPOXY-80	DN 80	88,9x2,0	4,3 kg	27,10 kg	Dažytas vamzdis, NF L=6000, 88,9 x 2,0	13,25
NF-EPOXY-100	DN 100	114,3x2,3	6,4 kg	38,40 kg	Dažytas vamzdis, NF L=6000, 114,3 x 2,3	19,64
NF-EPOXY-125	DN 125	139,7x2,9	9,8 kg	58,80 kg	Dažytas vamzdis, NF L=6000, 139,7 x 2,9	32,79
NF-EPOXY-150	DN 150	168,3x2,9	11,9 kg	71,30 kg	Dažytas vamzdis, NF L=6000, 168,3 x 2,9	36,59
NF-EPOXY-200	DN 200	219,1x3,6	19,1 kg	114,6 kg	Dažytas vamzdis, NF L=6000, 219,1 x 3,6	59,18

Vamzdynai priešgaisrinėms sistemoms

**Sriegtas vamzdis, dažytas RAL 7012, 3m / 6m, CE / PED 97/23 EEC. ISO 7/1
EN10226-1 / EN10226-2**



Kodas	DN	Dyxt	Svoris/m	Svoris/6m	Aprašymas	Kaina
NF-EPOXY-25-K3	DN 25	33,7x3,2	2,41 kg	7,23 kg	Dažytas vamzdis. EN10255 NF L=3000, 33,7 x 3,2 Sriegtas	9,77
NF-EPOXY-25-K6	DN 25	33,7x3,2	2,41 kg	14,46 kg	Dažytas vamzdis. EN10255 NF L=6000, 33,7 x 3,2 Sriegtas	8,72
NF-EPOXY-32-K3	DN 32	42,4x3,2	3,1 kg	9,30 kg	Dažytas vamzdis. EN10255 NF L=3000, 42,4 x 3,2 Sriegtas	12,57
NF-EPOXY-32-K6	DN 32	42,4x3,2	3,1 kg	18,60 kg	Dažytas vamzdis. EN10255 NF L=6000, 42,4 x 3,2 Sriegtas	11,22